

BOX PATENT APPLICATION
ASSISTANT COMMISSIONER FOR PATENTS
Washington, D.C. 20231

FORM PTO-1082
Case Docket No. 51270-245585
Date: November 10, 1998
Express Mail Label No. EL073550281US

Sir:

Transmitted herewith for filing is the patent application of
Inventor(s): **Sadayuki Narusawa, Hiromi Imura and Shuichi Esaki**
For: **Audio System Utilizing Personal Computer**

Enclosed are:

- ☒ 4 Sheet(s) of drawings (☒ formal ☐ informal)
☒ An assignment of the invention to Yamaha Corporation.
☐ An associate power of attorney.
☐ A verified statement to establish small entity status under 37 CFR 1.9 and 1.27.
☒ Declaration and Power of Attorney.
☒ Certified copy of Japan Patent Application No. 9-313062 filed November 14, 1997 from which
priority is claimed under 35 USC §119.
☐ IDS enclosed. ☐ with references.
☐ Preliminary Amendment

JC523 U.S. PTO
09/189768
11/10/98

CALCULATION OF FEES						
ITEM		NO. OF CLAIMS FILED MINUS BASE*	NO. OF CLAIMS OVER BASE	X SM/LG ENTITY FEE	\$ AMOUNT	\$ FEE
A	TOTAL CLAIMS FEE	20 - 20* =	0	X \$11 or X \$22	\$22	\$0
B	INDEPENDENT CLAIMS FEE**	6 - 3* =	3	X \$41 or X 82	\$82	
C	SUBTOTAL - ADDITIONAL CLAIMS FEE (ADD FINAL COLUMN IN LINES A + B)					\$246
D	MULTIPLE-DEPENDENT CLAIMS FEE				SMALL ENTITY FEE = \$135 LARGE ENTITY FEE = \$270	\$
E	BASIC FEE*				SMALL ENTITY FEE = \$395 LARGE ENTITY FEE = \$790	\$790
F	TOTAL FILING FEE (ADD TOTALS FOR LINES C, D, AND E)					\$1,036
F	ASSIGNMENT RECORDING FEE				\$ 40	\$40
**LIST INDEPENDENT CLAIMS 1, 2, 9, 10, 11 and 12						

☐ Please charge my Deposit Account No. 16-1805 the amount of \$0

☒ A check in the amount of \$1,036

☒ A check in the amount of \$40

**A copy of this letter is
enclosed.**

to cover the filing fee is
enclosed.

to cover Assignment
Recordation fee is enclosed.

X The Commissioner is hereby authorized to charge payment of the following fees associated with this communication or credit any overpayment to Deposit Account No. 16-1805.

X Any additional filing fees required under 37 CFR 1.16.

X Any patent application processing fees under 37 CFR 1.17.


— The Commissioner is hereby authorized to charge payment of the following fees during the pendency of this application or credit any overpayment to Deposit Account No. 16-1805.

— Any patent application processing fees under 37 CFR 1.17.

— The issue fee set in 37 CFR 1.18 at or before mailing of the Notice of Allowance, pursuant to 37 CFR 1.311(b).

— Any filing fees under 37 CFR 1.16 for presentation of extra claims.

Respectfully submitted,



Roger R. Wise
Reg. No. 31,204

Date: November 10, 1998

PILLSBURY MADISON & SUTRO LLP
725 South Figueroa Street, Suite 1200
Los Angeles, CA 90017-5443
Telephone: (213) 488-7100
Facsimile: (213) 629-1033

11/10/98
JCS40 U.S. PTO

Express Mail Label No.: EL073550281US

PATENT
Attorney Docket No.: 51270-245585

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants: Sadayuki Narusawa, et al.

Ar Unit: Not Assigned

Serial No.: Unknown

Examiner: Not Assigned

Filed: November 10, 1998

For: Audio System Utilizing Personal Computer

CERTIFICATE OF MAILING VIA U.S. EXPRESS MAIL

Date of Deposit: November 10, 1998

BOX PATENT APPLICATION

Assistant Commissioner for Patents
Washington, D.C. 20231

Dear Sir:

I hereby certify that

- ☒ Letter of transmittal
- ☒ check in amount of \$ 1,036 as filing fee
- ☒ patent application (16 pages of specification; 20 claims; 1 pages of abstract
- ☒ 4 sheet(s) of formal drawings
- ☒ executed Declaration and Power of Attorney
- ☒ executed Assignment, with Recordation Cover Letter and check in amount of \$40
- ☒ certified copy of Japanese priority document No. 9-313062 from which priority is claimed in the subject case pursuant to 35 USC § 119
- ☒ return postcard

are being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service with sufficient postage under 37 CFR 1.10 on the date indicated above and are addressed to:

BOX PATENT APPLICATION

Assistant Commissioner for Patents
Washington, D.C. 20231.

November 10, 1998

Date of Deposit

Liliana Rios

Name of person mailing papers

Liliana Rios

Signature

09139768 111098

AUDIO SYSTEM UTILIZING PERSONAL COMPUTER

BACKGROUND OF THE INVENTION

Field of the Invention

This invention relates to audio systems that are configured by connecting computers such as personal computers (PCs) and portable computers to audio devices such as audio component stereo sound systems equipped with speakers.

This application is based on Patent Application No. Hei 9-313062 filed in Japan, the content of which is incorporated herein by reference.

Description of the Related Art

According to the general configuration method employed by the audio system that is configured by connecting the personal computer (or PC) and audio device, output of a sound board of the personal computer is merely connected to an external input terminal of the audio device. In that method, the personal computer is placed as one source of the audio device. For this reason, when the audio device selects another source such as a FM tuner and a CD player, the audio device cannot reproduce audio signals from the personal computer. In this case, a user of the audio device cannot hear alarm sound and/or sound to inform receipt of electronic mail given from the personal computer. The aforementioned audio system is designed to employ a simple configuration that the personal computer merely outputs analog audio signals to the audio device. Such a configuration is incapable of effectively interconnecting (or interlocking) the personal computer with the audio device.

SUMMARY OF THE INVENTION

It is an object of the invention to provide an audio system in which an audio device is capable of reproducing audio data given from a personal computer without troubles even if the audio device selects a source other than the personal computer.

It is another object of the invention to provide an audio system that is capable of effectively interconnecting (or interlocking) the personal computer with the audio device.

An audio system of this invention is constructed by a personal computer and an audio device, which are connected together by way of a serial bus such as a universal serial bus (USB), for example. The audio device such as an audio component stereo system provides at least one audio source such as a tuner and a recording media, which provides first audio data representing music or else. The personal computer uses graphical user interface (GUI) for controlling operation of the audio data, wherein it provides control data and second audio data representing message sounds, which are transmitted to the audio device via the serial bus. Thus, the audio device performs mixing between the first audio data and second audio data on the basis of the control data. Then, speakers produce sounds based on mixing result.

In one aspect of the invention, the audio device is equipped with an analog mixing circuit, which performs analog mixing between analog signals corresponding to the first and second audio data respectively. Herein, signal processing (e.g., graphic equalizer process and/or sound field

control process) is performed on one of the first and second audio data, which is selected according to needs. Then, the analog mixing is performed between first analog signals corresponding to signal processing result and second analog signals corresponding to the second audio data. When the signal processing is selectively performed on the second audio data, it is possible to disconnect supply of the second analog signals to the analog mixing circuit.

In another aspect of the invention, the audio device is equipped with a digital mixing circuit, which performs digital mixing between the first and second audio data.

Thus, the user is capable of hearing the message sounds while listening to the music provided from the audio source, for example.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other objects, aspects and embodiment of the present invention will be described in more detail with reference to the following drawing figures, of which:

FIG. 1 shows an appearance of an audio system in accordance with embodiment of the invention;

FIG. 2 is a function block diagram showing blocks used for audio control made by a personal computer shown in FIG. 1;

FIG. 3A shows an example of an operation panel which is displayed on a screen of a display unit of the personal computer shown in FIG. 1;

FIG. 3B shows an example of a pull-down panel which appears on the screen when MIX is designated;

FIG. 3C shows another example of the operation panel which shows sound field images for sound field control in addition to switches and sections of the operation panel of FIG. 3A;

FIG. 4 is a block diagram showing an example of a configuration of an audio device shown in FIG. 1; and

FIG. 5 is a block diagram showing another example of the configuration of the audio device.

DESCRIPTION OF THE PREFERRED EMBODIMENT

This invention will be described in further detail by way of examples with reference to the accompanying drawings.

FIG. 1 shows an appearance of an audio system in accordance with the embodiment of the invention.

The audio system of FIG. 1 is configured by a personal computer 1, an audio device 2 such as an audio component stereo sound system, which are connected together by a single serial bus cable 3 and its interface(s).

The personal computer 1 is capable of linking with networks such as Internet and LAN (i.e., Local Area Network) by way of a communication line 4. Audio data and control data are transmitted in a bidirectional manner between the personal computer 1 and the audio device 2 by way of the serial bus cable 3. As the serial bus, it is preferable to use the USB (i.e., Universal Serial Bus). Or, it is possible to use other serial buses such as IEEE 1394 serial bus (i.e., a serial interface for computer networks, where "IEEE" is an abbreviation for "Institute of Electrical and Electronics Engineers"), for example. In addition, it is possible to use different cables

for transmission of the control data and audio data respectively. For example, a RS-232C cable is used for transmission of the control data, while SPDIF (i.e., normal digital interface such as optical cable) is used for transmission of the audio data.

The personal computer 1 is configured by a main body 11 containing a CPU (not shown), a keyboard 12, a mouse 13 and a display unit 14, which displays operation panels for manipulation of the audio device 2. The audio device 2 is configured by a main body unit 15 containing a tuner, a (CD) player and an amplifier as well as left/right loudspeakers 16, 17.

FIG. 2 is a function block diagram showing functions (or operations) regarding audio control of the personal computer 1.

The personal computer 1 is configured by hardware as well as software such as OS (i.e., operating system) and application programs. Thus, the personal computer 1 is configured by a GUI unit 21 (where "GUI" is an abbreviation for "Graphical User Interface"), a control data processing unit 22, an audio data processing unit 23, an audio data storage unit 24 and a serial bus interface (I/F) 25. The GUI unit 21 displays on a screen of the display unit 14 necessary operation panels, which are required to perform all of the operations of the audio device 2 by the personal computer 1. In addition, the GUI unit 21 performs processing to accept inputs from input devices such as the mouse 13.

FIG. 3A, FIG. 3B and FIG. 3C show an example of operation panels.

The operation panel of FIG. 3A contains five switches and three sections for adjustments, all of which can be selected and manipulated by click operations of the mouse 13. Specifically, the operation panel provides

a power switch 31 for ON/OFF control of power to the audio device 2, a PC switch 32 for selection of audio sources, a CD switch 33, a TUNER switch 34 and an AUX switch 35. In addition, the operation panel provides a MUTE adjuster 36 for adjustment of mute level, a MIX adjuster 37 for adjustment of mixing level established between the personal computer 1 and other audio sources, and a balance adjuster 38 for adjustment of tone volume balance between the loudspeakers 16 and 17.

When a user clicks the mouse 13 to designate the switch 33, 34 or 35 for selection of CD, TUNER or AUX as audio source, audio data given from the personal computer 1 are output by way of a mixing circuit, which will be described later. If the user clicks the mouse 13 to designate the MIX adjuster 37, a mixing level adjustment panel 39 shown in FIG. 3B is provided in a pull-down manner. Herein, by manipulating the mouse 13 to operate a control bar 40, it is possible to adjust a tone-volume ratio between the personal computer 1 and other audio source.

Using the benefits of the operation panels provided by the GUI unit 21, it is possible to perform a variety of setting operation by using graphic images. For example, FIG. 3C shows sound field images for sound field control, which are displayed in addition to the aforementioned switches and sections of the operation panel of FIG. 3A. Using those sound field images, it is possible to perform the setting of the desired sound field in an extremely easy way. When the user selects CD, it is possible to display an image representing information such as designation of a CD within CDs stored in a CD tray and a presently reproduced part of audio data recorded on the designated CD. Thus, the user is capable of confirming such

information with ease.

Of course, the audio device 2 is capable of being equipped with the aforementioned operation panel(s). However, there is a limit in provision of the image display. Because the personal computer 1 is capable of performing a variety of operations, it may be preferable to provide the audio device 2 with a limited number of operation switches used for basic functions only.

Based on operation information representing the operation(s) which is performed using the GUI unit 21, the control data processing unit 22 creates control data for operating the audio device 2. The control data are transmitted to the audio device 2 via the serial bus interface 25. In order to match operations made by the audio device 2 with contents of the operation panels of the personal computer 1, contents of the operations are reflected in the operation panels provided by the GUI unit 21 on the basis of control data given from the audio device 2.

The personal computer 1 selected by the GUI unit 21 provides the audio data processing unit 23 with output instructions such as the music stored in the personal computer 1 as well as the start/end sounds, alarm sound, inquiry sound and mail reception sound (hereinafter, all referred to as message sounds). So, the audio data processing unit 23 selects necessary audio data from the audio data storage unit 24 on the basis of the output instructions given from the personal computer 1. Then, the audio data processing unit 23 converts them to suit a digital data form which can be subjected to transmission. Thus, it outputs them to the audio device 2 via the serial bus interface 25.

FIG. 4 is a block diagram showing a configuration of a main body of the audio device 2.

As audio sources, the audio device 2 is equipped with a tuner unit 41, an analog AUX input unit 42, a digital AUX input unit 43 and a CD unit 44. The tuner unit 41 extracts signals of a desired channel from AM/FM signals received by an antenna 45. The tuner unit 41 and the analog AUX input unit 42 output respective analog audio signals, one of which is selected by a switch 46 and is converted to digital signals by an analog-to-digital converter 47 (abbreviated by A/D converter or ADC). The digital AUX input unit 43 and the CD unit 44 output respective digital audio data, one of which is selected by a multiplexer (abbreviated by MPX or MUX) 48 and is input to a digital interface receiver (abbreviated by DIR) 49. The digital interface receiver (DIR) 49 reproduces clock signals from the digital audio data input thereto. Using the reproduced clock signals, the digital interface receiver 49 extracts certain data from the input digital audio data. In addition, it separates control bits from the extracted data. Incidentally, the digital interface receiver 49 verifies the sampling frequency (and other parameters) so as to make determination as to whether the input data are reliable ones or not.

Output of the A/D converter 47 and output of the digital interface receiver 49 are subjected to selection made by a multiplexer 50, an output of which is then forwarded to a signal processing block 51. In other words, one of the digital audio data given from the A/D converter 47 and the digital interface receiver 49 respectively is selected and supplied to the signal processing block 51. The signal processing block 51 performs a graphic

equalizer process and a sound field control process on the selected digital audio data. Then, the processed digital audio data are converted to analog signals by a digital-to-analog converter (abbreviated by D/A converter or DAC) 52. The aforementioned circuit elements that range from the audio sources to the D/A converter 52 configure a first system portion of the audio system of the present embodiment.

Audio data and control data, which are given from the personal computer 1 via the serial bus cable 3 are input to a serial bus interface unit 53 shown in FIG. 4. The serial bus interface unit 53 separates the audio data and control data from the input data thereof. In the case where the serial bus corresponds to the universal serial bus (USB), a data format is constructed using a frame of 1 milli-second as a basic unit thereof. By detecting a start-of-frame (SOF), it is possible to extract its following frames. Thus, it is possible to separate the audio data and control data. In the case where the serial bus corresponds to the IEEE 1394 serial bus, it is possible to separate the audio data and control data by detecting self-ID packet which starts by codes of "10".

The separated audio data are subjected to digital-to-analog conversion by a D/A converter 54. The aforementioned circuit elements such as the serial bus interface unit 53 and the D/A converter 54 construct a second system portion of the audio system. Outputs of the D/A converters 52 and 54 are subjected to mixing performed by a mixing circuit 55. The mixing circuit 55 is configured by an electronic volume 56, resistors 57 and 58. Herein, the electronic volume 56 performs adjustment of a tone volume with respect to analog signals given from the D/A converter 54, while the

resistors 57 and 58 are provided for analog addition. A switch 59 is provided prior to the electronic volume 56 in such a way that the second system portion is subjected to analog mute and is placed in a mixing-off state. Output of the mixing circuit 55 is forwarded to an electronic volume 60 which adjusts master volume and is then output to the loudspeakers 16 and 17 via an amplifier 61.

Incidentally, the audio data separated by the serial bus interface unit 53 are selectively supplied to the first system portion as well via the multiplexer 50.

The control data separated by the serial bus interface unit 53 are supplied to a system control unit 62. Thus, the system control unit 62 produces control signals C1, C2, ..., C9 based on the foregoing operation information made by the GUI unit 21 of the personal computer 1. The control signals C1, C2 and C3 are supplied to the switch 46, multiplexer 48 and multiplexer 50 respectively. Thus, those control signals are used for selection of the audio source, which is designated. The control signal C4 is supplied to the switch 59, so that mixing is turned off in the case where the personal computer 1 is selected as the audio source. The control signals C5 and C6 control the electronic volumes 56 and 60 respectively. Further, the control signal C7 represents signal processing selection information for the signal processing block 51; the control signal C8 represents channel selection information for the tuner unit 41; and the control signal C9 represents selection information for the CD unit 44. Incidentally, operation switches 63 equipped in the audio device 2 are capable of supplying control data to the system control unit 62. Herein, contents of

operations of the operation switches 63 are displayed by a display 64 as well.

When the CD is selected as the audio source, the multiplexer 48 selects output of the CD unit 44, while the multiplexer 50 selects output of the digital interface receiver 49. At this time, the switch 59 operates to establish connection between the D/A converter 54 and the mixing circuit 55. So, when the personal computer 1 supplies the audio device 2 with a message sound while the user listens to sounds of the CD, the mixing circuit 55 mixes the message sound and CD sounds, which are produced by the speakers 16 and 17.

When the personal computer 1 is selected as the audio source, the multiplexer 50 selects the serial bus interface unit 53. Audio data given from the personal computer 1 are digital data, which have no deterioration in sound quality. In addition, the signal processing block 51 performs the graphic equalizer process and sound field process on the audio data. Therefore, it is possible for the user to appreciate the music of good quality. By the way, the personal computer 1 is equipped with a CD-ROM unit, which is capable of reproducing a CD used for the music. In that case, digital data reproduced from the CD are transmitted to the audio device 2 via the serial bus interface unit 53. Thus, it is possible to reproduce sounds of the music CD in a completely same manner that the audio component stereo system reproduces the music CD by itself. Incidentally, it is possible to make the setting of the personal computer 1 such that the message sounds (e.g., alarm sound and mail receipt sound) supplied from the personal computer 1 are adequately convoluted into the audio data with

ease. Those sounds are naturally produced by the speakers 16 and 17. Therefore, the audio system of the present embodiment is capable of avoiding an event that the user cannot hear the message sounds while listening to other audio sounds. In the aforementioned case where the message sounds are convoluted into the audio data, the switch 59 operates to disconnect the D/A converter 54 from the mixing circuit 55. As described before, the audio signals output from the first system portion are subjected to signal processing such as the sound field process, while the audio signals output from the second system portion are not been subjected to such signal processing but are subjected to simple digital-to-analog conversion. In the above case, it is possible to avoid an event that the audio signals of the first system portion are mixed with the audio signals of the second system portion. So, the present embodiment does not suffer from inconveniences such as jamming. In addition, the present embodiment is capable of effectively utilizing signal processing of a further high quality.

Incidentally, the present embodiment is designed to perform "analog" mixing. Of course, it is possible to modify the present embodiment to perform "digital" mixing using digital data. FIG. 5 is a block diagram showing a modified configuration of the audio device 2 that actualizes the digital mixing.

In the case of FIG. 5, it is necessary to make adjustments on sampling parameters such as sampling rates and sampling timings at input and output of the signal processing block 51. For this reason, output of the serial bus interface unit 53 is supplied to a sampling rate comparator (abbreviated by "SRC") 71, wherein it is subjected to frequency adjustment

and synchronization adjustment. Then, a mixing circuit 72 performs mixing between output of the sampling rate comparator 71 and output of the signal processing block 51. The mixing circuit 72 is configured by a mixing digital volume 73 and an adder 74. The mixing circuit 72 is followed by a master digital volume 75. The foregoing signal processing circuit 51, mixing circuit 72 and master digital volume 75 are all designed as digital circuits. Therefore, it is possible to configure them in a form of a single signal processing block 76. Output of the master digital volume 75 is subjected to digital-to-analog conversion by a D/A converter 77, output of which is then supplied to the speakers 16, 17 via the amplifier 61.

As the audio device 2, the present embodiment employs an audio component stereo system of an integrated type, which incorporates a variety of sources therein. Of course, it is possible to employ single component units respectively. Or, it is possible to employ an amplifier-incorporated speaker (or so-called PC speaker), which has a serial bus terminal and an external input terminal.

Lastly, effects of the invention will be described as follows:

- (1) The audio system of the invention is constructed by a personal computer and an audio device, which are connected together by way of a serial bus. Herein, the audio device performs mixing between audio data of the personal computer and audio data given from an audio source differed from the personal computer. Therefore, the user is capable of hearing contents of the audio data of the personal computer representing message sounds such as alarm sound and mail reception sound while listening to sounds of the audio source.

(2) The audio device of the audio system is designed to contain a first system portion and a second system portion. Herein, the first system portion provides the high-class digital audio processing such as the equalizing process and hall sound field imparting control process, while the second system portion provides only the simple processing such as the digital-to-analog conversion, for example. The audio data of the personal computer can be supplied to either the first system portion or second system portion. So, even when the first system portion selects the audio source other than the personal computer, in other words, even when the first system portion does not process the audio data of the personal computer, the user is capable of hearing the message sounds, which are subjected to mixing from the second system portion. If the audio data of the personal computer represent musical tone data having a high sound quality that is equivalent to the CD and the like, the first system portion selects the personal computer as the audio source so that the sound processing of high precision is performed on the audio data of the personal computer in a manner similar to sound processing for the other audio source. In that case, the user is capable of hearing the message sounds processed in the first system portion. So, the mixing effected between outputs of the first and second system portions are prohibited, so that only the processing system of a higher quality (i.e., first system portion) is effectively utilized. In addition, it is possible to avoid unexpected inconveniences such as the jamming.

- (3) The personal computer is capable of displaying operation panels.

So, control data are produced based on operations of the operation panels and are transmitted via the serial bus to control operations of the audio device. Or, the personal computer receives information regarding operations made by the audio device, which is then reflected in contents of the operation panels. So, even if the audio device is located far from the personal computer, the personal computer is capable of performing all of the operations made by the audio device. Thus, it is possible to improve handling extremely well in audio control. In addition, all the operations made by the audio device are reflected in contents of the operation panels of the personal computer. Therefore, there is no inconsistency in operations between the personal computer and audio device.

- (4) This invention is applicable to the audio component stereo system, which incorporates the AM/FM tuner and player for CD (compact disk), MD (mini disk), DAT (digital audio tape) etc. In addition, this invention is applicable to the so-called PC speaker that is constructed by the amplifier and speaker(s).

- (5) The contents of the audio system of this invention are described as the audio control program. The audio control program can be provided for the user in a form of the recording media such as the CD and floppy disk(s), or it can be provided using communications from the host computer, for example. The audio control program is basically designed to include software elements as follows:

- (i) Graphical user interface (GUI), which is provided on the display

of the personal computer to control operations of the audio device such as the selection of the audio source and the mixing for the audio data of the selected audio source and audio data of the personal computer;

(ii) Process that control data are produced based on operations made by the graphical user interface and are output to the audio device; and

(iii) Process that information regarding the operations made by the audio device is received and is reflected in contents of the graphical user interface.

As this invention may be embodied in several forms without departing from the spirit of essential characteristics thereof, the present embodiments are therefore illustrative and not restrictive, since the scope of the invention is defined by the appended claims rather than by the description preceding them, and all changes that fall within metes and bounds of the claims, or equivalence of such metes and bounds are therefore intended to be embraced by the claims.

What is claimed is:

1. An audio system comprising:

an audio device;

a computer for creating audio data and control data for operating the audio device; and

data transmission means for linking the audio device and the computer together to transmit data therebetween,

wherein said computer has output means for outputting the audio data and the control data to the audio device via the data transmission means,

while said audio device further comprises

a first system portion for processing audio data that are given from an audio source differed from the audio data of the computer,

a second system portion for processing the audio data given from the computer, and

mixing means for performing mixing for a plurality of the audio data, which are respectively processed by the first and second system portions.

2. An audio system comprising:

an audio device;

a computer for creating audio data and control data for operating the audio device; and

data transmission means for linking the audio device and the computer together to transmit data therebetween,

wherein said computer has output means for outputting the audio data and the control data to the audio device via the data transmission means,

while said audio device further comprises

a first system portion for performing signal processing on audio data given from the computer, or for performing the signal processing on audio data of an audio source differed from the audio data of the computer or audio data selectively given from one of a plurality of audio sources differed from the computer,

a second system portion for performing simple signal processing, which is simple as compared with the signal processing of the first system portion, on the audio data given from the computer,

mixing means for performing mixing for a plurality of the audio data, which are respectively processed by the first and second system portions, and

means for turning off the mixing of the mixing means when the first system portion performs the signal processing selectively on the audio data of the computer.

3. An audio system according to claim 1, wherein the computer further comprises

display means for displaying an operation panel for operating the audio device,

means for outputting the control data to the audio device via the data transmission means on the basis of operation of the operation panel,

means for receiving information regarding operation made by the audio device via the data transmission means as the control data so as to reflect it in content of the operation panel, and

means for outputting the audio data to the audio device via the data transmission means.

4. An audio system according to claim 2, wherein the computer further comprises

display means for displaying an operation panel for operating the audio device,

means for outputting the control data to the audio device via the data transmission means on the basis of operation of the operation panel,

means for receiving information regarding operation made by the audio device via the data transmission means as the control data so as to reflect it in content of the operation panel, and

means for outputting the audio data to the audio device via the data transmission means.

5. An audio system according to claim 1, wherein the data transmission means is configured by a single serial bus cable and its interface.

6. An audio system according to claim 2, wherein the data transmission means is configured by a single serial bus cable and its

interface.

7. An audio system according to claim 3, wherein the data transmission means is configured by a single serial bus cable and its interface.

8. An audio system according to claim 4, wherein the data transmission means is configured by a single serial bus cable and its interface.

9. An audio device comprising:
at least one audio source;
an interface for inputting audio data supplied from a computer;
audio processing means for processing audio data given from the audio source and the audio data given from the computer;
mixing means for performing mixing between the audio data processed by the audio processing means and the audio data which are input thereto via the interface; and
speaker means for producing sound based on output of the mixing means.

10. An audio device comprising:
input means for inputting audio data supplied from an audio source differed from a computer;
an interface for inputting audio data supplied from the computer;

mixing means for performing mixing between the audio data input by the input means and the audio data which are input thereto via the interface; and

speaker means for producing sound based on output of the mixing means.

11. A machine-readable media storing an audio control program that causes a computer to actualize an audio control system comprising:

graphical user interface means for operating the audio device, the graphical user interface means actualizing an operation to select an audio source for the audio device and an operation to perform mixing on audio data of the selected audio source and audio data given from the computer;

means for outputting control data to the audio device on the basis of operation of the graphical user interface means;

means for receiving information regarding operation of the audio device as the control data so as to reflect it in content of graphical user interface; and

means for outputting the audio data to the audio device.

12. An audio system comprising:

an audio device for producing first audio data in connection with at least one audio source,

serial bus means, and

a personal computer for producing second audio data and control data,

wherein the audio device performs mixing between the first audio data and the second audio data, which are transmitted thereto via the serial bus means, on the basis of the control data, so that speaker means produces sound based on mixing result.

13. An audio system according to claim 12, wherein the audio device further comprises

selection means for selecting one of the first audio data and the second audio data,

signal processing means for performing signal processing on output of the selection means,

first digital-to-analog conversion means for converting output of the signal processing means to first analog signals,

second digital-to-analog conversion means for converting the second audio data given from the personal computer to second analog signals, and

analog mixing means for performing analog mixing between the first analog signals and the second analog signals,

whereby the speaker means produces sound based on result of the analog mixing.

14. An audio system according to claim 13, wherein the audio device further comprises

switch means for disconnecting the second digital-to-analog means from the analog mixing means when the selection means selects the second audio data.

15. An audio system according to claim 12, wherein the audio device further comprises
- selection means for selecting one of the first audio data and the second audio data,
 - signal processing means for performing signal processing on output of the selection means,
 - adjustment means for performing adjustment on the second audio data with respect to sampling parameters,
 - digital mixing means for performing digital mixing between output of the signal processing means and output of the adjustment means, and
 - digital-to-analog conversion means for converting result of the digital mixing to analog signals,
- whereby the speaker means produces sound based on the analog signals.
16. An audio system according to claim 12, wherein the serial bus means corresponds to a universal serial bus.
17. An audio system according to claim 12, wherein the serial bus means corresponds to an IEEE 1394 serial bus.
18. An audio system according to claim 12, wherein the audio source corresponds to a tuner or a recording media.

19. An audio system according to claim 12, wherein the personal computer uses graphical user interface (GUI) for creation of the control data for controlling operation of the audio device.

20. An audio system according to claim 12, wherein the signal processing corresponds to a graphic equalizer process and/or a sound field control process.

04/03/2004 10:00:00

ABSTRACT OF THE DISCLOSURE

An audio system is constructed by a personal computer and an audio device, which are connected together by way of a serial bus such as a universal serial bus (USB), for example. The audio device such as an audio component stereo system provides at least one audio source such as the tuner and recording media, which provides first audio data representing music or else. The personal computer uses graphical user interface (GUI) for controlling operation of the audio data, wherein it provides control data and second audio data representing message sounds, which are transmitted to the audio device via the serial bus. Thus, the audio device performs mixing between the first audio data and second audio data on the basis of the control data. Then, speakers produce sounds based on mixing result. The audio device is equipped with an analog mixing circuit, which performs analog mixing between analog signals corresponding to the first and second audio data respectively. Or, the audio device is equipped with a digital mixing circuit, which performs digital mixing between the first and second audio data. Thus, the user is capable of hearing the message sounds while listening to the music provided from the audio source of the audio device, for example.

FIG.1





FIG.2






FIG.3A




FIG.3B






FIG.3C





**DECLARATION
and POWER OF ATTORNEY**

☒ ORIGINAL
☐ CONTINUATION
☐ DIVISIONAL

As a below named inventor, I declare that the information given herein is true, that I believe that I am the original, first and sole inventor if only one name is listed at 1 below, or a joint inventor if plural inventors are named below at 1-6, for the invention entitled:

AUDIO SYSTEM UTILIZING PERSONAL COMPUTER

Which is described and claimed in:

- ☒ the attached specification or
☐ the specification in application Serial No. _____ filed _____
☐ as amended on _____ (for declaration not accompanying application, if applicable)

and for which a patent is sought, and that my residence, post office address and citizenship are as stated below next to my name.

I acknowledge my duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations §1.56.

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I hereby claim priority benefits under Title 35, United States Code, §119 of any application(s) for patent or inventor's certificate listed below and have also identified below any application(s) for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

PRIOR APPLICATION(S)

COUNTRY	APPLICATION NUMBER	DATE OF FILING Month Day Year	PRIORITY CLAIMED UNDER 35 U.S.C. §119	
			YES <input checked="" type="checkbox"/>	NO <input type="checkbox"/>
Japan	Patent 9-313062	11/14/1997	YES <input type="checkbox"/>	NO <input type="checkbox"/>

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application.

(Application Serial No.) (Filing Date) (Status)

POWER OF ATTORNEY:

As a named Inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith:

Paul N. Kokulis, Reg. No. 16,773
Raymond F. Lippitt, Reg. No. 17,519
G. Lloyd Knight, Reg. No. 17,698
George M. Sirilla, Reg. No. 18,221
Carl G. Love, Reg. No. 18,781
Kevin E. Joyce, Reg. No. 20,508
Edgar H. Martin, Reg. No. 20,534
David W. Brinkman, Reg. No. 20,817
William K. West, Jr., Reg. No. 22,057
Edward M. Prince, Reg. No. 22,429
G. Paul Edgell, Reg. No. 24,238
Donald J. Bird, Reg. No. 25,323
Peter W. Gowdey, Reg. No. 25,872
W. Warren Taltavull, Reg. No. 26,647
Richard H. Zaitlen, Reg. No. 27,248
Glenn J. Perry, Reg. No. 28,458

Dale S. Lazar, Reg. No. 28,872
Kendrew H. Colton, Reg. No. 30,368
Mark G. Paulson, Reg. No. 30,793
Barry L. Grossman, Reg. No. 30,844
John P. Moran, Reg. No. 30,906
Paul E. White, Jr., Reg. No. 31,097
Roger R. Wise, Reg. No. 31,204
Stephen C. Glazier, Reg. No. 31,361
Paul F. McQuade, Reg. No. 31,542
Jeffrey A. Simenauer, Reg. No. 31,933
Michelle N. Lester, Reg. No. 32,331
David A. Jakopin, Reg. No. 32,995
Timothy J. Klima, Reg. No. 34,852
Paul H. Kovelman, Reg. No. 35,228
Lynn E. Eccleston, Reg. No. 35,861
Paul G. Nagy, Reg. No. 37,896
Stephen Bongini, Reg. No. 40,917

Send correspondence to:

Roger R. Wise

Pillsbury Madison & Sutro, LLP

725 South Figueroa Street, Suite 1200

Los Angeles, CA 90017-5443

DIRECT TELEPHONE CALLS TO:

(213) 488-7584 (direct line)

(213) 488-7100 (general line)

1	Name of Inventor	LAST NAME Narusawa	FIRST NAME Sadayuki	MIDDLE NAME	Residence: CITY Hamamatsu-shi	STATE or COUNTRY Japan
	Post Office Address c/o YAMAHA CORPORATION, 10-1, Nakazawa-cho, Hamamatsu-shi, Shizuoka-ken, Japan					CITIZENSHIP Japan
2	Name of Inventor	LAST NAME Imura	FIRST NAME Hiromi	MIDDLE NAME	Residence: CITY Hamamatsu-shi	STATE or COUNTRY Japan
	Post Office Address c/o YAMAHA CORPORATION, 10-1, Nakazawa-cho, Hamamatsu-shi, Shizuoka-ken, Japan					CITIZENSHIP Japan
3	Name of Inventor	LAST NAME Esaki	FIRST NAME Shuichi	MIDDLE NAME	Residence: CITY Hamamatsu-shi	STATE or COUNTRY Japan
	Post Office Address c/o YAMAHA CORPORATION, 10-1, Nakazawa-cho, Hamamatsu-shi, Shizuoka-ken, Japan					CITIZENSHIP Japan
4	Name of Inventor	LAST NAME	FIRST NAME	MIDDLE NAME	Residence: CITY	STATE or COUNTRY
	Post Office Address					CITIZENSHIP
5	Name of Inventor	LAST NAME	FIRST NAME	MIDDLE NAME	Residence: CITY	STATE or COUNTRY
	Post Office Address					CITIZENSHIP
6	Name of Inventor	LAST NAME	FIRST NAME	MIDDLE NAME	Residence: CITY	STATE or COUNTRY
	Post Office Address					CITIZENSHIP

I further declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

SIGNATURE OF INVENTOR 1 <i>Sadayuki Narusawa</i>	SIGNATURE OF INVENTOR 2 <i>Hiromi Imura</i>
DATE: <i>1998 Oct. 31</i>	DATE: <i>1998 Oct. 31</i>
SIGNATURE OF INVENTOR 3 <i>Shuichi Esaki</i>	SIGNATURE OF INVENTOR 4
DATE: <i>1998 Oct. 31</i>	DATE:
SIGNATURE OF INVENTOR 5	SIGNATURE OF INVENTOR 6
DATE:	DATE: